

Product Specifications

FlashLink PDF Elite In-Transit Logger

Measurement Range	-40°F to 140°F (-40°C to 60°C)
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F/± 0.5°C from -40°F to 140°F (-40°C to 60°C)
Data Capacity	32,000 data points
Data Download Time	5 seconds typical
Factory Programmable Alarm Levels	High/low limits over entire temperature range
Battery	Coin Cell Lithium battery
Dimensions	3.9in x 1.7 in x 0.5 in (99.1mm x 43.2mm x 12.7mm)
Casing	ABS plastic
Weight	1.28 oz (36.29 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant
Display	LCD, trip statistics, red LED alarm and high/low limit indicators
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
PDF Standards	Complies with ISO19005-1, PDF/A, 21 CFR Part 11
System Requirements	Windows PC with current operating system, Adobe Reader
Download Requirements	Direct USB connection



Models	40060	40061	40062	40063	40064	40065	40066	40067	40068
Alarm Settings	Low: 15°C High: 25°C	Low: 2°C High: 8°C	Low: -25°C High: -15°C	Low: 15°C High: 30°C	Low: 2°C High: 25°C	Low: -25°C High: 8°C	Low: 2°C High: 8°C	Low: 15°C High: 25°C	Low: -25°C High: -15°C
Logging Interval	15 Minutes						5 Minutes		
Duration	45 Day						42 Day		
Start Delay	60 Minutes						15 Minutes		
Time Zone	GMT								

- Single-use Temperature Logger
- Large, easy to ready LCD display
- No software required to download data
- Automatically creates secure PDF report and CSV file
- Trip history statistics available on LCD
- Patented Shadow Log® feature guarantees data even if the shipper fails to start the logger
- Toggle between °F/°C temperature scale
- Service available to custom configure logging parameters, alarms, delayed start

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS_4006X_25E2

